

DH Series

www.fluorel.co.uk/products/recessed.htm

DH
Series



11/11



Decorative and
architectural energy
efficient recessed
downlighters

FluorelLighting
Lighting for a brighter future

**Fluorel Lighting is a leading supplier
of innovative energy efficient lighting**

DH Series

Recessed Downlighters

Ideal for a wide variety of applications these downlighters feature cast aluminium bezels and super pure internal reflector



DHM

Quality downlighter with diamond faceted super pure reflector.

Product Ref	Lamps	Weight
6.721018L	1x18w TC-DEL	1.13kg
6.722018L	2x18w TC-DEL	1.13kg
6.721026L	1x26w TC-DEL	1.13kg
6.722026L	2x26w TC-DEL	1.13kg

Dimensions: Ø192mm H.145mm ⌀176mm ▽IP20



DHTM

Quality downlighter with super pure turbo type louvre attachment giving controlled cut off and low glare.

Product Ref	Lamps	Weight
6.641018L	1x18w TC-DEL	1.36kg
6.642018L	2x18w TC-DEL	1.36kg
6.641026L	1x26w TC-DEL	1.36kg
6.642026L	2x26w TC-DEL	1.36kg

Dimensions: Ø237mm H.209mm ⌀222mm ▽IP20



DOHM

Quality downlighter with decorative drop opal polycarbonate attachment with chromed conical fixings.

Product Ref	Lamps	Weight
6.721018L/DG008	1x18w TC-DEL	1.36kg
6.722018L/DG008	2x18w TC-DEL	1.36kg
6.721026L/DG008	1x26w TC-DEL	1.36kg
6.722026L/DG008	2x26w TC-DEL	1.36kg

Dimensions: Ø192mm H.145mm ⌀176mm ▽IP20



DHWM

Downlighter with wall washer attachment for feature or asymmetric light distribution.

Product Ref	Lamps	Weight
6.621018L/WWW	1x18w TC-DEL	1.13kg
6.622018L/WWW	2x18w TC-DEL	1.13kg
6.621026L/WWW	1x26w TC-DEL	1.13kg
6.622026L/WWW	2x26w TC-DEL	1.13kg

Dimensions: Ø192mm H.145mm ⌀176mm ▽IP20



Life

Very shallow closed downlighter with decorative toughened front glass.

Product Ref	Lamps	Weight
DHLF218HFL	2 x 18w TC-DEL	1.5kg
DHLF226HFL	2 x 26w TC-DEL	1.5kg

Dimensions: Ø230mm H.125mm ⌀215mm ▽IP20



Splash

Downlighter with etched halo and decorated toughened drop glass attachment. This model is also available in IP54 version.

Product Ref	Lamps	Weight
DHSP218HFL	2 x 18w TC-DEL	1.7kg
DHSP226HFL	2 x 26w TC-DEL	1.7kg
DHSP218HFL/IP54	2 x 18w TC-DEL	1.7kg
DHSP226HFL/IP54	2 x 26w TC-DEL	1.7kg

Dimensions: \varnothing 230mm H.160mm \otimes 215mm ∇ IP20 or IP54 as indicated



Extra

Shallow Square downlighter with etched toughened front glass.

Product Ref	Lamps	Weight
DHEX218HFL	2 x 18w TC-DEL	2.2kg
DHEX226HFL	2 x 26w TC-DEL	2.2kg

Dimensions: 230x230mm H.125mm \otimes 205x205mm ∇ IP20/23



Fox

Square downlighter with etched halo and clear toughened drop glass attachment.

Product Ref	Lamps	Weight
DHFX218HFL	2 x 18w TC-DEL	2.2kg
DHFX226HFL	2 x 26w TC-DEL	2.2kg

Dimensions: 247x247mm H.130mm \otimes 205x205mm ∇ IP20



Living

Square downlighter with etched toughened drop glass attachment.

Product Ref	Lamps	Weight
DHLV218HFL	2 x 18w TC-DEL	2.2kg
DHLV226HFL	2 x 26w TC-DEL	2.2kg

Dimensions: 247x247mm H.130mm \otimes 205x205mm ∇ IP20



Tekno

Square downlighter with soft curved profile etched toughened drop glass attachment.

Product Ref	Lamps	Weight
DHTE218HFL	2 x 18w TC-DEL	2.2kg
DHTE226HFL	2 x 26w TC-DEL	2.2kg

Dimensions: 260x260mm H.110mm \otimes 205x205mm ∇ IP20

DH

Series



- All luminaires are supplied with lamps* and suspension kits.
- Emergency versions are available - suffix /EMG when ordering.
- Self Test emergency versions are available – suffix /STEMG when ordering.
- Please contact Fluorel or see www.fluorel.co.uk for photometric data.
- Fluorel recommend the use of support trays or reinforcement if using downlighters in very soft fibrous ceiling materials.

LongLast™

- 1,200,000 minutes or 2.5 years of continuous light
Rated Average Life for Biax™ LongLast Q/E, D/E and T/E lamps is 20000 hours (switching cycle:11 Hrs ON/1 Hr OFF).
- Energy saving without loss of light output
- Low energy consumption
- LongLast lamp life up to 20x longer than incandescent lamps
- 80% savings over incandescent lamps
- Triple tube ultra compact design
- Reduces operating costs
- Low mercury content

T5WattMiser™

2DWattMiser™

LongLast™

*Where possible Fluorel recommend the use of GE lamps.

Fluorel Lighting Limited
Designers and manufacturers
of lighting fittings

Unit 3, 2-8 Roebuck Road,
Hainault, Essex IG6 3UE.
Tel +44(0)8458 643 643 Fax +44(0)20 8506 1792
info@fluorel.co.uk www.fluorel.co.uk

FluorelLighting
Lighting for a brighter future